

## Aluminium strip for tubes 制管用铝材

\* Various specifications for B-TUBES、ratio-frequency welded tubes and other tubes

适合各种规格的 B 型管，高频焊管以及其他管子

\* Good surface condition and slitting precision

良好的表面质量以及剪切精度

\* Excellent collapse resistance during brazing

良好的钎焊抗塌陷性能

\* Perfect corrosion resistance and long life

优秀的抗腐蚀性能以及使用寿命



B-tube and ratio-frequency welded tube B 型管以及高频焊管性能指标							
Alloy 牌号	Temper 状态	Thickness (mm) 厚度	Tolerance (mm) 公差	Clad rate(%) 复合层	Mechanical property 机械性能		
					Tensile Strength (MPa) 抗拉强度	Yield Strength (MPa) 屈服强度	Elongation Min.(%) 延伸率
4343/SA-5/ 7072	H24	0.25~0.3	±0.008	8~12	160~210	≥120	5
4343/SA-7/ 7072	H24	0.25~0.3	±0.008	8~12	170~220	≥120	5
Glass mounting bracket material 玻璃支架用管料性能指标							
Alloy 牌号	Temper 状态	Thickness (mm) 厚度	Tolerance (mm) 公差	Clad rate(%) 复合层	Mechanical property 机械性能		
					Tensile Strength (MPa) 抗拉强度	Yield Strength (MPa) 屈服强度	Elongation Min.(%) 延伸率
3003	H26	0.3~35	±0.015	None	190~220	≥160	8
<p>* 4343 can be replaced by 4045/4047 etc, according to customer's requirement. 4343 可以根据客户需要被 4045、4047 等代替。</p> <p>* Slitting tolerance can be controlled in ±0.02mm. 剪切精度可以控制在±0.02mm.</p> <p>* Alloy、specification and mechanical property can be customized according to different requirement. 合金以及规格、性能可根据用户需求另行制定。</p>							